

Silikonska creva, profili i gajtani





- Silikonska creva**-izradjuju se u prečniku od fi 2-50mm,
- debljina zida 0,5-30mm
- temperatura primene: -50°C do 290°C
- boja -transparentna ili obojena

Primena: transport prehrambenih tečnosti, pare, transport medicinskih fluida, presvlačenje valjaka u farmaceutskoj industriji, ostala primena gde se traži otpornost na povišene temperature .

-**Silikonska armirana creva**

- silikonska creva se armiraju da bi izdržala povišene pritiske do 80 bara
 - uslovi rada: -50°C do 290°C
 - primena-transport pregrejane pare, agresivnih fluida i medija u farmaceutskoj, prehrambenoj, hemijskoj industriji, transport medicinskih fluida pod pritiskom.
- Isporučuju se creva sa opletom spolja kao i sa armaturom u zidu creva.

Tehničke karakteristike:

- Hardness: 60-80° Shore 'A' po DIN 53505
- Tensile strength: 11 N/mm² po DIN 53504
- Elongation At Break; 490% po DIN 53504
- Density : 1.2 g/cm³
- T- - 50 do 290 C

SILIKONSKI PROFILI ZA ZAPTIVANJE VRATA



TERMOPLAST
silikonski profili

	1	<p>B=0,3mm – 25mm A=2,2mm – 35mm</p>
	2	<p>A=25mm B=12mm C=8mm</p>
	3	<p>A=28mm A=30mm B=17mm B=25mm C=15mm C=28mm</p>
	4	<p>A=20mm B=17mm C=8mm</p>

IZRAĐUJEMO SILIKONSKE PROFILE PO UZORKU I CRTEŽU
SILIKON TVRDOĆE OD 40 DO 80 SH
TEMPERATURNI OPSEG DO 300°

	5	<p>A=8mm B=3mm C=3mm</p>
	6	<p>A=12mm B=7mm C=3mm</p>
	7	<p>A=28mm B=28mm C=28mm</p>
	8	<p>A=15mm B=15mm</p>
	9	<p>A=8mm B=8mm C=3mm</p>

IZRAĐUJEMO SILIKONSKE PROFILE PO UZORKU I CRTEŽU
SILIKON TVRDOĆE OD 40 DO 80 SH
TEMPERATURNI OPSEG DO 300°

	10	<p>A=25mm B=12mm</p>
	11	<p>A=8mm B=2mm C=3mm</p>
	12	<p>A=14mm A=20mm B=14mm B=15mm</p>
	13	<p>A=20mm B=20mm C=15mm</p>
	14	<p>A=8mm B=8mm C=3mm D=3mm</p>

IZRAĐUJEMO SILIKONSKE PROFILE PO UZORKU I CRTEŽU
SILIKON TVRDOĆE OD 40 DO 80 SH
TEMPERATURNI OPSEG DO 300°

TERMOPLAST silikonski profili



35

A=17mm
B=22mm
C=35mm



36

A=28mm
B=35mm



37

A=20mm
B=25mm



38

A=25mm
B=32mm
C=25mm



39

A=18mm
B=15mm

IZRAĐUJEMO SILIKONSKE PROFILE PO UZORKU I CRTEŽU
SILIKON TVRDOĆE OD 40 DO 80 SH
TEMPERATURNI OPSEG DO 350°

TERMOPLAST silikonski profili



20

A=18mm
B=25mm
C=22mm



21

A=18mm
B=18mm



22

A=18mm
B=18mm



23

A=17mm
B=11mm
C=25mm



24

A=18mm
B=18mm

IZRAĐUJEMO SILIKONSKE PROFILE PO UZORKU I CRTEŽU
SILIKON TVRDOĆE OD 40 DO 80 SH
TEMPERATURNI OPSEG DO 350°

TERMOPLAST silikonski profili



25

A=15mm
B=10mm
C=10mm
D=5mm



26

A=13mm
B=10mm



27

A=18mm
B=12mm



28

A=12mm
B=14mm



29

A=12mm
B=12mm
C=12mm

IZRAĐUJEMO SILIKONSKE PROFILE PO UZORKU I CRTEŽU
SILIKON TVRDOĆE OD 40 DO 80 SH
TEMPERATURNI OPSEG DO 350°

TERMOPLAST silikonski profili



30

A=20mm - 22mm
B=20mm - 22mm



31

A=18mm
B=20mm
C=18mm



32

A=18mm - 20mm



33

A=18mm
B=18mm



34

A=18mm - 20mm

IZRAĐUJEMO SILIKONSKE PROFILE PO UZORKU I CRTEŽU
SILIKON TVRDOĆE OD 40 DO 80 SH
TEMPERATURNI OPSEG DO 350°